



Product Data Sheet ***Tacky Mats*** ***1.5 mil, vinyl backing***

2008

<i>Mat Layers:</i>	<i>Low Density Polyethylene</i>
<i>Mat Layer Thickness:</i>	<i>.0015" (1.5 mils)</i>
<i>Mat Layer Adhesive:</i>	<i>Acrylic Copolymer Formulation, 7-10 oz./in.width(nominal) adhesion on #4 stainless steel (for standard tack product)</i>
<i>Mat Sizes:</i>	<i>Actual mat size is .25" less than nominal size.(i.e. 18"x45" mats are actually finished at 17.75" x 44.75")</i>
<i>Backing Material:</i>	<i>Low Density Polyethylene</i>
<i>Backing Thickness:</i>	<i>.004 (mils)</i>
<i>Backing Adhesive:</i>	<i>Solvent based acrylic both sides</i>
<i>Peel tabs:</i>	<i>Polyester - alternating white/blue</i>
<i>Applications:</i>	<i>Entrances of any controlled environment such as clean rooms, laboratories and other applications</i>
<i>Adhesion Properties:</i>	<i>High tack Moderate-Fast Adhesion buildup Adheres to most hard surface floors</i>

The above data is for reference only, actual results may vary with test conditions. Customers are urged to conduct their own tests under conditions relevant to their application.